



## The IBUC Advantage

All IBUCs are equipped with cutting-edge intelligent technology:

- Highest quality & exacting performance guaranteed through individual unit testing over temperature
- Superior linearity for maximum useable output power
- Amplifier overdrive protection
- User-selectable AGC/ALC for optimal performance & compatibility with modem adaptive coding
- New high capacity microprocessor & extended M&C functions
- Weatherized RJ45 Ethernet interface for simplified connection

### ULTIMATE MANAGEMENT & CONTROL

- » Local Web Interface & NMS-Friendly SNMP «
- » 70+ User Configurable Thresholds & Alarms «
- » Upgraded Event Log with 1,000 Sensor Readings «
- » Performance Trend Analysis Tools & Statistical logs «
- » Embedded Web Pages for Universal Web Browser Access «

## C-Band IBUC G

400W/500W GaN IBUC for multicarrier application.



New Cyber Hardened version available	Multicarrier Application	400W P <sub>Lin</sub> 200W & 500W P <sub>Lin</sub> 250W	GaN Tech Amplifier	3 Year Warranty
--------------------------------------	--------------------------	---	--------------------	-----------------

## Applications

The new IBUC G now supports multicarrier transmission across the full C-band spectrum. The IBUC G delivers the highest available output power, making it an ideal solution for high data rate multicarrier applications such as maritime, broadband, broadcast and network hubs. The 400W model produces +53 dBm of linear output power, and the 500W model produces +54 dBm of linear output power.

Gallium Nitride amplifier technology enables smaller packaging for antenna mounting, eliminating the losses in long waveguide runs. And the greater power efficiency translates to an appreciable reduction in power consumption. Comparing favorably with earlier technology TWTAs, the GaN IBUC G delivers maximum linear output power with the reliability of solid state.

### Options

- 1+1 Transmit Redundancy with Eco-Mode
- High Stability Internal 10 MHz Reference with Auto-Detection
- Mounting Brackets
- N-Type, F-Type or TNC Input Connectors
- Handheld Terminal
- Cyber Hardened
- WGS (Wideband Global SATCOM) compatible.

**Note:** Since not all the optional features can be combined, please, contact our sales team for further info at: [Sales@Terrasatinc.com](mailto:Sales@Terrasatinc.com)

# C-Band 400W/500W IBUC G for Multicarrier Application

Frequency Range	RF (MHz)	IF (MHz)	
Sense		Inverting	Non-Inverting
Band 1 Std C	5850 to 6425	950 to 1525	950 to 1525
Band 2 Palapa	6425 to 6725	975 to 1275	1125 to 1425
Band 3 Insat	6725 to 7025	1150 to 1450	965 to 1265
Band 4 Ext C	5850 to 6650	950 to 1750	950 to 1750
Band 5 Full C	5850 to 6725	975 to 1850	950 to 1825

  

Input	
VSWR/ Impedance	1.5:1 / 50 Ohm
Input Connector	Type N Female (50 Ohm)
Input Connector Options	Type F (75 Ohm), TNC (50 Ohm)
Input Power Detector Range options:	
Standard Version	-50 to -15 dBm
WGS Version	-35 to 0 dBm

  

Gain		
Small Signal Gain (L-band to RF) with attenuator set to 0 dB options:		
Standard Version	WGS Version	
400W 82 dB min	76 dB min	
500W 83 dB min	77 dB min	
Attenuator Range	30 dB variable in 0.1 dB steps	
Gain Flatness		
Full Band	4 dB p-p max	
36 MHz	1.5 dB p-p max	
1 MHz	0.25 dB p-p	
Gain Variation Over Temperature		
	<u>Bands 1/2/3</u>	<u>Bands 4/5</u>
Open Loop	3 dB p-p max	4 dB p-p max
With AGC	1 dB p-p max	1 dB p-p max

  

RF Output		
Interface	CPR-137G	
VSWR	1.3:1 max	
Output Power		
	<u>400W</u>	<u>500W</u>
	Band 1	Bands 2/3/4/5
at P <sub>sat</sub> (typ)	+56 dBm	+55.5 dBm
at P <sub>lin</sub> (min)	+53 dBm	+52.5 dBm
	Band 1	Bands 2/3/4/5
	+57 dBm	+56.5 dBm
	+54 dBm	+53.5 dBm
19 dB min of NPR (Noise Power Ratio) at:	50 dBm	49.5 dBm
	51 dBm	50.5 dBm

P<sub>lin</sub> is the maximum linear power as defined by MIL STD 188-164C  
Two-tone measured at 5MHz and 150 MHz spacing

Level stability with ALC	± 0.5 dB
Output power detector range	Rated power to -20 dB
Power reading accuracy	± 1.0 dB max.
Spurious @P <sub>lin</sub>	
In Band	-70 dBc
Out of Band	Complies with EN 301 443 & MIL-STD 188-164C
Harmonics @ P <sub>lin</sub>	-50 dBc max.
Output Noise Power Density	
	Tx < - 75 dBm/Hz
	Rx < - 145 dBm/Hz

SSB Phase Noise	External Reference	IBUC G
10 Hz	-115 dBc/Hz	-54 dBc/Hz
100 Hz	-140 dBc/Hz	-79 dBc/Hz
1 KHz	-150 dBc/Hz	-89 dBc/Hz
10 KHz	-155 dBc/Hz	-94 dBc/Hz
100 KHz	N/A	-100 dBc/Hz
1 MHz	N/A	-110 dBc/Hz

### External Reference (Multiplexed on TX IFL)

Frequency & Level                      10 MHz                      -12 to +5 dBm

Internal Reference- Optional

### Local Oscillator Frequency

Sense	Inverting	Non-Inverting
Band 1	7375 MHz	4900 MHz
Band 2	7700 MHz	5300 MHz
Band 3	8175 MHz	5760 MHz
Band 4	7600 MHz	4900 MHz
Band 5	7700 MHz	4900 MHz

### IBUC Power Supply

Voltage	AC	200 to 240 VAC			
Power Consumption		Band 1		Bands 2/3/4/5	
		<u>400W</u>	<u>500W</u>	<u>400W</u>	<u>500W</u>
at P <sub>sat</sub>		1900 VA	2100 VA	1850 VA	2000 VA
at P <sub>lin</sub>		1500 VA	1650 VA	1750 VA	1550 VA

### Monitor & Control - For Standard Versions

Ethernet (HTTP, Telnet, SNMPv2c) via RJ45 Connector

RS232/485, Handheld Terminal via MS-Type Connector

FSK multiplexed on TX IFL

### Monitor & Control - For Cyber Hardened Versions

Ethernet (HTTPS, SSHv2, SNMPv3 with USM and VACM) via RJ45 Connector

RS232 via MS-Type Connector

XSS (Cross Site Scripting)

Two NTP Servers Providing Redundancy

FIPS 140-2 compatible.

The Cyber Hardened versions have embedded new high-end Cyber Security features, from hardware to software, including a new controller board and the new firmware. For further details, refer to the Cyber Hardened IBUCs' datasheet at [www.terrasatinc.com/products/](http://www.terrasatinc.com/products/)

### Environmental

Operating Temperature	-40°C to +55°C
Relative Humidity	100% Condensing
Altitude	10,000 ft (3,000 m) ASL

### Mechanical

Weight	40 lbs
	18 kg
Size	24 x 10 x 7.4 in.
	610 x 254 x 188 mm

Specifications subject to change without notice.

Updated April 11th, 2022

## Questions? Contact Us

1+(408) 782-5911

[Sales@TerrasatInc.com](mailto:Sales@TerrasatInc.com)

315 Digital Drive  
Morgan Hill, CA 95037  
[www.TerrasatInc.com](http://www.TerrasatInc.com)