

TRENDnet Gigabit PoE+ Injector (Model TPE-115GI)

Overview & Specifications

Standards

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3ab
- IEEE 802.3af (PoE)
- IEEE 802.3at (PoE+)

Device Interface

- 1 x Gigabit Data In port
- 1 x Gigabit Data & Power Out port
- LED Indicators for power status

Special Features

- Wall-mountable design

Data Transfer Rate

- Ethernet: 10 Mbps (half duplex), 20 Mbps (full duplex)
- Fast Ethernet: 100 Mbps (half duplex), 200 Mbps (full duplex)
- Gigabit: 2000 Mbps (full duplex)

PoE Delivery

- Pin 1, 2 for Power+
- Pin 3, 6 for Power- (Mode A)

Power

- Input: 100-240 V AC, 50/60 Hz, 0.6A max

TRENDnet Gigabit PoE+ Injector (Model TPE-115GI)

- Power Consumption: Max 1.03 W (no powered device connected)

Operating Environment

- Temperature: 0 - 40 degreesC (32 - 104 degreesF)
- Humidity: Max 90% non-condensing

Physical Dimensions

- Size: 155 x 57 x 33 mm (6.1 x 2.3 x 1.3 in)
- Weight: 188 g (6.64 oz)

Certifications

- CE
- FCC

Warranty

- 3 years

Package Contents

- TRENDnet Gigabit PoE+ Injector (TPE-115GI)
- Quick Installation Guide
- Power Cord