2320005012

HDMI Encoder 8X

HDMI Encoder 8X



Description

The HDMI Encoder 8X is a professional HDMI H.264 encoder. It is equipped with 8 HDMI inputs, 1 IP output, and 1 ASI input for re-mux. It is ideal for encoding signals from DVB receivers, DVD & Blu-ray players, from MPEG-2 to H.264 or vice versa.

www.zenitel.com info@zenitel.com Last revision date: 2025-01-06 14:32

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL

Mounting	Rack Mountable, 1HU
Weight	4 Kg
Dimensions (WxHxD)	440x44x410 mm
Power supply	100–240 Volts, 50–60 Hz
Power consumption	25W
IP rating	IP20

INPUTS/OUTPUTS

8 x HDMI inputs
1x ASI input
1x ASI input
1x IP output
1x Gigabit Ethernet 10/100/1000 Mb/s

www.zenitel.com info@zenitel.com Last revision date: 2025-01-06 14:32

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

PERFORMANCE

MPEG-4 AVC/H.264 encoding	
Supports multiplexing function	
0.8 Mbps - 19 Mbps each channel	
Supported resolution:	
1920x1080_60P / 1920x1080_50P	
1920x1080_60i / 1920x1080_50i	
1280x720_60P / 1280x720_50P	
720x576_50i / 720x480_60i	

CONTROL & ADMINISTRATION

Front panel LCD	
Network management system (NMS)	

www.zenitel.com info@zenitel.com Last revision date: 2025-01-06 14:32

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.